

Application: pedestrians, bicycle routes, parkings, tunnels and underground passages

Assembly: on extension arms with $\varnothing 60 \times 90$ mm ending

Ingress protection: IP 66 for the optical part and the driver

Material: anodised aluminium alloy

Colour: inox / black

Optical system: PMMA optics

Number of LEDs: 12

Operating temperature range: from -40°C to $+55^{\circ}\text{C}$

Expected useful lifetime: L90F10 – 50 000 h, L80F20 – 100 000 h

CRI: >80 for 5000K, 3500K; >70 for 5000K, 4000K


Corrective factor S/P: 1,8 for 5000K; 1,45 for 3500K; 1,55 for 4000K

Input voltage frequency: 50 - 60Hz


Power factor: ≥ 0.95

Inrush current: : 50A / 210 μs

Luminaire. LED has the possibility to connect to an external control system via analog signal 1- 10V.









Code	Symbol	LED power	Power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ¹⁾	Luminaire luminous flux ¹⁾	Luminous efficacy	Unit volume	Luminaire net weight
213230/3	LED 24	24W	31W	760mA	3500K	3 450lm	3200lm	103lm/W	0,005m ³	2,2kg
213230/4	LED 24	24W	31W	760mA	4000K	3 850lm	3700lm	119lm/W	0,005m ³	2,2kg
213230/6	LED 24	24W	31W	760mA	5000K	4 050lm	3900lm	126lm/W	0,005m ³	2,2kg
213232/3	LED 36	36W	39W	960mA	3500K	4 550lm	4300lm	110lm/W	0,005m ³	2,2kg
213232/4	LED 36	36W	39W	960mA	4000K	5 050lm	4600lm	118lm/W	0,005m ³	2,2kg
213232/6	LED 36	36W	39W	960mA	5000K	5 250lm	4800lm	123lm/W	0,005m ³	2,2kg



1) tolerance +/- 7% due to LEDs accuracy

Directive: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC



Overcurrent switches MCB type B or C

Luminaire	Typ	2A	4A	6A	10A	16A	20A	25A
ISKRA LED	B	1	2	4	6	11	13	17
	C	1	4	6	11	18	28	28

Fuse – type gG and GL

Luminaire	2A	4A	6A	10A	16A	20A	25A
ISKRA LED	1	2	11	19	30	38	47